



Ocean VH200

Ocean Machines

Ocean Machines has made a commitment to its customers to change the landscape for packaging equipment.

The packaging market is getting more competitive every day.

We are dedicated to bringing you top quality packaging equipment, manufactured in Asia, with all the support you can expect from your equipment supplier: full warranty, qualified support and local spare parts which can be sourced from our 24 hour online parts warehouse.

Ocean Machines supplies their packaging equipment with high-end components. Leading component suppliers like Mitsubishi, Festo, Omron, Schneider and many more are proud business partners of Ocean Machines.

Please visit www.oceanmachines.com for information on our complete product portfolio.





	Ocean V150	Ocean V200 / VH200	Ocean V250 / VH250*
Packaging Type	Pillow Bag / Gusseted Bag	Pillow Bag / Gusseted Bag	Pillow Bag / Gusseted Bag
Maximum Speed	60 per minute	60 or 100 per minute	60 or 100 per minute
Bag Width	50-150mm	80-200mm	80-250mm
Bag Length	80-200mm	60-300mm	80-350mm
Maximum Reel Width	320mm	420mm	520mm
Power Requirements	220V / 50Hz / 2.0kW	220V / 50Hz / 2.2kW	220V / 50Hz / 2.5kW
Air Consumption	0.3 cbm/min. / 0.8Mpa	0.5 cbm/min. / 0.8Mpa	0.5 cbm/min. / 0.8Mpa
Dimensions (LxWxH)	1150x800x1370mm	1458x920x1392mm	1500x1140x1540mm
Weight	300kg	500kg	700kg



	Ocean V350	Ocean V500	Ocean VB240
Packaging Type	Pillow Bag / Gusseted Bag	Pillow Bag / Gusseted Bag	Quad Seal
Maximum Speed	45 per minute	30 per minute	40 per minute
Bag Width	160-350mm	300-500mm	Front 100-240mm Side 50-150mm
Bag Length	100-450mm	100-800mm	100-420mm
Maximum Reel Width	730mm	1050mm	700mm
Power Requirements	220V / 50Hz / 4.5kW	220V / 50Hz / 6kW	220V / 50Hz / 4kW
Air Consumption	0.8 cbm/min. / 0.6Mpa	0.8 cbm/min. / 0.6Mpa	0.3 cbm/min. / 0.8Mpa
Dimensions (LxWxH)	1360x1630x1900mm	2250x1800x2400mm	1700x1550x2200mm
Weight	900kg	1000kg	980kg



	Ocean SL	Ocean MLB	Ocean HS
Model	3/4 Sided or Stickpack	4 Sided or Stickpack	3/4 Sided Seal
Stations / Lanes	1	4 to 6	1
Maximum Speed	60 per minute	40 per Lane per minute	70 per minute
Filling Range	0-1000ml	1-20ml	60-400ml
Bag Width	Max. 150 / 200 or 250mm	16-35mm	Max. 110 / 130 or 180mm
Bag Length	Max. 240 / 310 or 390mm	50-140mm	Max. 130 / 180 / 225mm
Power Requirements	380V / 50Hz / 2.5kW	220V / 50Hz / 3.2kW	380V / 50Hz / 4.5kW
Air Consumption	0.6 cbm/min. / 0.8Mpa	0.1 cbm/min. / 0.8Mpa	0.1 cbm/min. / 0.7Mpa
Dimensions (LxWxH)	1235x1090x1600mm	1120x1023x1380mm	3500x970x1450mm
Weight	400kg	610kg	1600kg