



Ocean VB240

### Ocean Machines

Ocean Machines has made a commitment to its customers to change the landscape for packaging equipment.

The packaging market is getting more competitive every day.

We are dedicated to bringing you top quality packaging equipment, manufactured in Asia, with all the support you can expect from your equipment supplier: full warranty, qualified support and local spare parts which can be sourced from our 24 hour online parts warehouse.

Ocean Machines supplies their packaging equipment with high-end components. Leading component suppliers like Mitsubishi, Festo, Omron, Schneider and many more are proud business partners of Ocean Machines.

Please visit [www.oceanmachines.com](http://www.oceanmachines.com) for information on our complete product portfolio.



Ocean VH150



Ocean VH200



Ocean VH250



Ocean V350



Ocean V500



Ocean VB240



Ocean SL



Ocean ML



Ocean HS



|                    | Ocean V150                | Ocean V200 / VH200        | Ocean V250 / VH250*       |
|--------------------|---------------------------|---------------------------|---------------------------|
| Packaging Type     | Pillow Bag / Gusseted Bag | Pillow Bag / Gusseted Bag | Pillow Bag / Gusseted Bag |
| Maximum Speed      | 60 per minute             | 60 or 100 per minute      | 60 or 100 per minute      |
| Bag Width          | 50-150mm                  | 80-200mm                  | 80-250mm                  |
| Bag Length         | 80-200mm                  | 60-300mm                  | 80-350mm                  |
| Maximum Reel Width | 320mm                     | 420mm                     | 520mm                     |
| Power Requirements | 220V / 50Hz / 2.0kW       | 220V / 50Hz / 2.2kW       | 220V / 50Hz / 2.5kW       |
| Air Consumption    | 0.3 cbm/min. / 0.8Mpa     | 0.5 cbm/min. / 0.8Mpa     | 0.5 cbm/min. / 0.8Mpa     |
| Dimensions (LxWxH) | 1150x800x1370mm           | 1458x920x1392mm           | 1500x1140x1540mm          |
| Weight             | 300kg                     | 500kg                     | 700kg                     |



|                    | Ocean V350                | Ocean V500                | Ocean VB240                   |
|--------------------|---------------------------|---------------------------|-------------------------------|
| Packaging Type     | Pillow Bag / Gusseted Bag | Pillow Bag / Gusseted Bag | Quad Seal                     |
| Maximum Speed      | 45 per minute             | 30 per minute             | 40 per minute                 |
| Bag Width          | 160-350mm                 | 300-500mm                 | Front 100-240mm Side 50-150mm |
| Bag Length         | 100-450mm                 | 100-800mm                 | 100-420mm                     |
| Maximum Reel Width | 730mm                     | 1050mm                    | 700mm                         |
| Power Requirements | 220V / 50Hz / 4.5kW       | 220V / 50Hz / 6kW         | 220V / 50Hz / 4kW             |
| Air Consumption    | 0.8 cbm/min. / 0.6Mpa     | 0.8 cbm/min. / 0.6Mpa     | 0.3 cbm/min. / 0.8Mpa         |
| Dimensions (LxWxH) | 1360x1630x1900mm          | 2250x1800x2400mm          | 1700x1550x2200mm              |
| Weight             | 900kg                     | 1000kg                    | 980kg                         |



|                    | Ocean SL                | Ocean MLB              | Ocean HS                |
|--------------------|-------------------------|------------------------|-------------------------|
| Model              | 3/4 Sided or Stickpack  | 4 Sided or Stickpack   | 3/4 Sided Seal          |
| Stations / Lanes   | 1                       | 4 to 6                 | 1                       |
| Maximum Speed      | 60 per minute           | 40 per Lane per minute | 70 per minute           |
| Filling Range      | 0-1000ml                | 1-20ml                 | 60-400ml                |
| Bag Width          | Max. 150 / 200 or 250mm | 16-35mm                | Max. 110 / 130 or 180mm |
| Bag Length         | Max. 240 / 310 or 390mm | 50-140mm               | Max. 130 / 180 / 225mm  |
| Power Requirements | 380V / 50Hz / 2.5kW     | 220V / 50Hz / 3.2kW    | 380V / 50Hz / 4.5kW     |
| Air Consumption    | 0.6 cbm/min. / 0.8Mpa   | 0.1 cbm/min. / 0.8Mpa  | 0.1 cbm/min. / 0.7Mpa   |
| Dimensions (LxWxH) | 1235x1090x1600mm        | 1120x1023x1380mm       | 3500x970x1450mm         |
| Weight             | 400kg                   | 610kg                  | 1600kg                  |